







PENDANT STATIONS -HP Series Price w.e.f.10.05.2023

- ➔ Laser Marked according EN 60204-1
- ➔ Operating temperature of -25°C~+70°C.
- ➔ Available in kit versions
- ➔ Available in UL/CSA requirements
- ➔ Shock proof and heat resistant
- ➔ IP65 Double Insulation(IEC/EN 60529)

PRODUCT	ITEM	SPECIFICATIONS	Part No	Rs
	ERGONOMIC 3 PUSH BUTTON HOIST PENDANT STATION	<ul style="list-style-type: none"> - Single or Double speed motor. - Bi-directionality is externally mechanical interlocked. - Double row ergonomic design. 	HP03	2395
			HP03.D2	2650
	ERGONOMIC 5 PUSH BUTTON HOIST PENDANT STATION	<ul style="list-style-type: none"> - Single or Double speed motor. - Bi-directionality is externally mechanical interlocked. - Double row ergonomic design. 	HP05	3220
			HP05.D2	3550
			HP05.D4	3880
	ERGONOMIC 7 PUSH BUTTON HOIST PENDANT STATION	<ul style="list-style-type: none"> - Single or Double speed motor. - Bi-directionality is externally mechanical interlocked. - Double row ergonomic design. 	HP07	4210
			HP07.D2	4375
			HP07.D4	4785
	ERGONOMIC 8 PUSH BUTTON HOIST PENDANT STATION	<ul style="list-style-type: none"> - Single or Double speed motor. - Bi-directionality is externally mechanical interlocked. - Double row ergonomic design. - Alarm/Start button 	HP08	4870
			HP08.D2	5450
			HP02.D4	5775
			HP08.D6	6105