





ROTARY GEAR LIMIT SWITCHES - **FGR 0**

w.e.f. 10.05.2023

- ➔ Standard or Flanged Fixing boxes.
- ➔ Available in different ratios under request.
- ➔ IP65 Protection Class.
- ➔ Can be supplied with Double Output Shaft.
- ➔ Available in 2 and 4 Contacts.
- ➔ Potentiometer or Encoder option.
- ➔ NC Contact Positive Opening.
- ➔ Self Lubricating cam-block with transparent support.
- ➔ 5 different cam shapes.
- ➔ 1NC-1NO Changeover Snap Action Contact Blocks.
- ➔ Operating temperature of -30°C~+70°C.
- ➔ 250V 8A.

  Base Flanged			
PRODUCT	SPECIFICATIONS	PART NO	INR
ROTARY GEAR LIMIT SWITCH 2 CONTACTS 1:50 RATIO	- 2x MFI.7STP contacts; - A PA66 Reinforced Casing.	FGR0-0050M-2B	3650
ROTARY GEAR LIMIT SWITCH 2 CONTACTS 1:100 RATIO	- 2x MFI.7STP contacts; - PA66 Reinforced Casing.	FGR0-0100M-2B	3950
ROTARY GEAR LIMIT SWITCH 2 CONTACTS 1:200 RATIO	- 2x MFI.7STP contacts; - PA66 Reinforced Casing.	FGR0-0200M-2B	4100
ROTARY GEAR LIMIT SWITCH 2 CONTACTS 1:400 RATIO	- 2x MFI.7STP contacts; - PA66 Reinforced Casing.	FGR0-0400M-2B	4250



GIOVENZANA
CONTROLS INDIA Pvt. Ltd.

ROTARY GEAR LIMIT SWITCH 4 CONTACTS 1:50 RATIO	- 4x MFI.7 contacts; - PA66 Reinforced Casing.	FGR-0050M-4B	4500
ROTARY GEAR LIMIT SWITCH 4 CONTACTS 1:100 RATIO	- 4x MFI.7 contacts; - PA66 Reinforced Casing.	FGR-0100M-4B	4800
ROTARY GEAR LIMIT SWITCH 4 CONTACTS 1:200 RATIO	- 4x MFI.7 contacts; - PA66 Reinforced Casing.	FGR-0200M-4B	4990
ROTARY GEAR LIMIT SWITCH 4 CONTACTS 1:400 RATIO	- 4x MFI.7 contacts; - PA66 Reinforced Casing.	FGR-0400M-4B	5200

OTHER PRODUCT



Pendant Station

Pendant Cable

102, A Wing, Knox Plaza, Off. Link Road, Mindspace,
Malad West, MUMBAI : 400064,
Maharashtra State, India
Tel: +91.22.42640071 - E-mail: ggindia@giovenzana.com
www.giovenzana.com



GIOVENZANA
CONTROLS INDIA Pvt. Ltd.

ROTARY GEAR LIMIT SWITCHES

FGR 1 & 2

- Available in different ratios under request.
- IP65 Protection Class .
- Can be supplied with Double Output Shaft.
- Available in 2 and 4 Contacts.
- Potentiometer or Encoder option.
- Self Lubrificating cam-block with transparent support.
- NC Contact Positive Opening.
- 1NC-1NO Changeover Snap Action Contact Blocks.
- Operating temp of -30 °C ~ +70 °C.
- 250V 8A

PRICE LIST

w.e.f 10.05.2023

			
PRODUCT	SPECIFICATIONS	PART NO	INR
ROTARY GEAR LIMIT SWITCH 2 CONTACTS 1:50 RATIO	- 2x MFI.7STP contacts; - PA6 Reinforced Casing.	FGR100502	3550
ROTARY GEAR LIMIT SWITCH 2 CONTACTS 1:100 RATIO	- 2x MFI.7STP contacts; - PA6 Reinforced Casing.	FGR101002	3625
ROTARY GEAR LIMIT SWITCH 2 CONTACTS 1:200 RATIO	- 2x MFI.7STP contacts; - PA6 Reinforced Casing.	FGR102002	3700
ROTARY GEAR LIMIT SWITCH 2 CONTACTS 1:400 RATIO	- 2x MFI.7STP contacts; - PA6 Reinforced Casing.	FGR104002	3875

102, A Wing, Knox Plaza, Off. Link Road, Mindspace,
Malad West, MUMBAI : 400064,
Maharashtra State, India
Tel: +91.22.42640071 - E-mail: ggindia@giovenzana.com
www.giovenzana.com



ROTARY GEAR LIMIT SWITCH 4 CONTACTS 1:50 RATIO	- 4x MFI.7 contacts; PA6 Reinforced Casing.	FGR100504	4025
ROTARY GEAR LIMIT SWITCH 4 CONTACTS 1:100 RATIO	- 4x MFI.7 contacts; - PA6 Reinforced Casing.	FGR101004	4200
ROTARY GEAR LIMIT SWITCH 4 CONTACTS 1:200 RATIO	- 4x MFI.7 contacts; - PA6 Reinforced Casing.	FGR102004	4350
ROTARY GEAR LIMIT SWITCH 4 CONTACTS 1:400 RATIO	- 4x MFI.7 contacts; - PA6 Reinforced Casing.	FGR104004	4500
FGR 2 Rotary Gear Limit Switch			
ROTARY GEAR LIMIT SWITCH 4 CONTACTS RATIO- 1:12	- - 4x MFI.7 contacts; - Aluminium Die Cast Base and PA66 Reinforced Casing.	FGR2N006	8050
RATIO-1:33		FGR2N007	8050
RATIO-1:50		FGR2N008	8050
RATIO-1:100		FGR2N009	8050
RATIO-1:200		FGR2N010	8400